



Chemical Pre-Flush and Additive Strategies to Enhance CO₂ Solubility and Injectivity in Deep Saline Aquifers: Mechanisms, Evidence, and Field Readiness

Mohammed Mahtab Ahmed¹, Amjed Hassan^{1,2}, Fahad Khan¹, Arshad Raza^{1,*}, Rahul Gajbhiye^{1,*} and Mohamed Mahmoud¹

¹Department of Petroleum Engineering, College of Petroleum Engineering & Geosciences, King Fahd University of Petroleum and Minerals, Dhahran 31261, Saudi Arabia

²Center for Integrative Petroleum Research, King Fahd University of Petroleum & Minerals, Dhahran 31261, Saudi Arabia

Abstract

Deep saline aquifers offer the largest global capacity potential for geologic carbon storage, yet storage performance is frequently constrained by coupled limitations on CO₂ dissolution (solubility trapping) and injectivity under high-salinity conditions. Elevated ionic strength suppresses CO₂ solubility via “salting-out” effects. Meanwhile, near-wellbore dry-out during injection of dry or undersaturated CO₂ can concentrate brine and precipitate salts, reducing permeability and injectivity. Mineralogy and CO₂-brine-rock wettability further control multiphase flow topology, interfacial area for dissolution, capillary trapping, and compatibility of additives with reservoir surfaces. This review critically evaluates chemical pre-flush and additive-enabled conditioning strategies intended to (i) increase

local aqueous CO₂ dissolution capacity, (ii) mitigate or prevent dry-out-driven salt precipitation and near-wellbore formation damage, and (iii) enhance CO₂-brine contact through mobility control. We synthesize and compare evidence for four strategy families: (1) freshwater and engineered low-salinity (LoSal) pre-flush slugs and intermittent re-wetting; (2) chelating agents (e.g., EDTA/GLDA/DTPA) that complex multivalent cations and alter dissolution/precipitation pathways; (3) surfactant-derived CO₂ foams, including CO₂-soluble surfactants designed for foam generation at the displacement front with achievable injectivity; and (4) nanoparticle-assisted and hybrid foam systems that extend foam stability under harsh salinity and temperature.

Keywords: deep saline aquifers, solubility trapping, salt precipitation, low-salinity pre-flush, chelating agents, CO₂ foam, CO₂-soluble surfactants, nanoparticles.



Submitted: 06 June 2026

Revised: 17 September 2026

Accepted: 18 September 2026

Published: 01 October 2026

Vol. 3, No. 1, 2027.

10.62762/RS.2026.344933

*Corresponding authors:

✉ Arshad Raza

arshad.raza@kfupm.edu.sa

✉ Rahul Gajbhiye

rahulg@kfupm.edu.sa

Citation

Ahmed, M. M., Hassan, A., Khan, F., Raza, A., Gajbhiye, R., & Mahmoud, M. (2026). Chemical Pre-Flush and Additive Strategies to Enhance CO₂ Solubility and Injectivity in Deep Saline Aquifers: Mechanisms, Evidence, and Field Readiness. *Reservoir Science*, 3(1), 1–25.



© 2026 by the Authors. Published by Institute of Central Computation and Knowledge. This is an open access article under the CC BY license (<https://creativecommons.org/licenses/by/4.0/>).

1 Introduction

The rapid increase in atmospheric carbon dioxide (CO₂) emissions has emerged as one of the most pressing global challenges of the 21st century. Fossil fuel combustion, industrial activity, and land-use changes have disrupted the natural carbon cycle, causing greenhouse gas levels to rise at unprecedented rates [1]. Global CO₂ emissions reached over 37 gigatons in 2024, with China, the United States, and India being the largest contributors [2, 3]. This imbalance has already produced measurable consequences, including rising sea levels, melting polar ice, and more frequent extreme weather events [4]. While renewable energy deployment and emissions-reduction policies are essential, many decarbonization pathways also rely on CCS to address residual and hard-to-abate emissions [5]. Carbon capture and storage (CCS) is widely recognized as a complementary mitigation pathway, capable of providing immediate reductions while long-term energy transitions are underway [6, 7].

CCS involves capturing CO₂ from stationary sources and securely injecting it underground into suitable formations [8]. Several storage options are available, including depleted oil and gas reservoirs, unmineable coal seams, basalt formations, and deep saline aquifers. Each offers unique benefits, such as proven trap integrity in hydrocarbon reservoirs or dual recovery potential in coal seams [9, 10]. However, saline aquifers stand out for their global abundance, immense theoretical capacity, measured in thousands of gigatons, and spatial overlap with major emission sources [11–13]. Practical demonstration projects have underscored their viability. For example, the Sleipner project in Norway has safely stored approximately 20 million tonnes (Mt) of CO₂ since 1996 [14, 15], while the Gorgon project in Australia is one of the world's largest integrated CCS facilities, with a projected lifetime storage of 129 Mt [16]. Together, these projects highlight both the opportunities and the operational challenges of saline aquifer storage.

A key advantage of deep saline aquifers is the range of trapping mechanisms they support. Structural and stratigraphic trapping beneath impermeable caprocks provides immediate containment, residual trapping immobilizes CO₂ in pore spaces, solubility trapping dissolves CO₂ into brine, and mineral trapping converts it into stable carbonates [17–19]. Among these, solubility trapping is especially significant because dissolved CO₂ increases brine density, reduces buoyancy-driven migration, and establishes the

conditions necessary for mineral precipitation [20, 21]. Long-term monitoring at Sleipner, for example, has shown that although only approximately 20–30% of injected CO₂ has dissolved into formation brine and less than 1% mineralizes, even this fraction plays a vital role in plume stabilization and injectivity control [14, 22]. Thus, improving solubility trapping directly strengthens the containment aspect of storage [23].

The effectiveness of solubility trapping is strongly influenced by pressure, temperature, and salinity [24]. High salinity reduces CO₂ solubility and promotes salt precipitation in the near-wellbore region, impairing permeability and injectivity [25–27]. In hypersaline systems, salt precipitation and early mineral precipitation can also reduce the pore volume available for dissolution [28, 29]. These issues compromise both short-term injectivity and long-term storage security. To mitigate such challenges, researchers have increasingly explored chemical pre-flush treatments, in which conditioning fluids are introduced into the aquifer before or during CO₂ injection to improve solubility trapping and minimize salt-related damage [30–32].

Several classes of pre-flush strategies have emerged to counter the effect of high salinity and enhance CO₂ solubility in brine. Freshwater or low-salinity injection can locally dilute brine and suppress salt deposition, as shown in simulation studies and at the Quest CCS project [26, 32, 33]. Chelating agents such as ethylenediaminetetraacetic acid (EDTA) and *N,N*-dicarboxymethyl glutamic acid (GLDA) can chelate multivalent cations, reduce scaling, and simultaneously accelerate carbonate mineralization [34–36]. Nanoparticles have been used to stabilize CO₂ foams, promote convective mixing, and modify wettability, with studies reporting up to 50% improvements in solubility trapping [37–39]. Surfactants, both water-soluble and CO₂-soluble, have shown promise in generating foams that enhance sweep efficiency and reduce gas mobility in saline aquifers [40–42]. Each method shows potential yet faces challenges related to cost, environmental compatibility, scalability, and reservoir heterogeneity [43, 44].

Despite encouraging laboratory findings, the real-world application of pre-flush treatments in CCS projects remains limited. Existing field-scale demonstrations, such as Sleipner and Gorgon, primarily rely on natural solubility processes, and deliberate chemical conditioning is uncommon in

Table 1. Selected geological CO₂ storage projects in saline aquifers [9, 45].

Ref.	Project	Estimated storage capacity	Description	Implications for pre-flush treatment
[46]	Nagaoka field, Japan	≈10 400 t injected (pilot, 2003-2005)	The Nagaoka pilot site is located in Niigata Prefecture, Japan. The project began in 2000, and CO ₂ was injected between 2003 and 2005; the storage process used CO ₂ and water injected in slugs. The site has a total depth of 1230 m, a storage thickness of 60 m, and handled injection rates of 20-40 t/day.	Water-alternating-gas (WAG) technique already acts as a built-in mitigation, so pre-flush is not considered.
[47]	Sleipner CCS, Norway	25 Mt	Owing to the Norwegian carbon tax, CO ₂ has been injected into the Utsira sandstone formation beneath an impermeable caprock in the North Sea at about 2800 t per day and approximately 800 m depth. The project showed that subsurface CO ₂ storage can operate effectively without significant operational problems.	A freshwater pre-flush may be adopted should injectivity losses occur, but this has not been necessary so far, according to monitoring data.
[16]	Gorgon field, Australia	129 Mt	The Gorgon CCS system on Barrow Island is one of the world's largest integrated capture and storage facilities. The project began in 2019 and has stored about 7 Mt of CO ₂ ; cumulative storage is expected to exceed 100 Mt over its operational lifetime. Naturally occurring CO ₂ separated from offshore gas reserves is injected into the Dupuy sandstone at depths of more than 2000 m. The storage interval lies about 2700 m below the surface with a thickness of 200-500 m, and the design injection rate is reported as 4.9 Mt per year.	Injectivity issues traced to salt precipitation may require a limited freshwater pre-flush or co-injection, if compatible with the clay structure, to avoid fines migration.
[48]	Jubail CCS Hub, Saudi Arabia	Up to 9 Mt/yr (Phase 1)	Joint venture (Aramco, SLB, Linde) aiming to be one of the largest CCS hubs in the region.	Pre-flush design depends entirely on characterization results such as salinity, mineralogy, permeability, and clay sensitivity.

practice [49, 50]. Field-scale gaps highlight the need for a consolidated review that compares methods, evaluates feasibility, and identifies pathways for scaling from laboratory to industrial application. Given the scale of global CO₂ emissions and the focus on saline aquifers in CCS strategies, systematic development of chemical pre-flush techniques is necessary. Therefore, this review discusses key approaches, such as the injection of freshwater, chelating agents, nanoparticles, and surfactants, while emphasizing their mechanisms, feasibility, limitations, and connections to mineral trapping. By consolidating findings across experimental, modeling, and early field work, this paper provides a framework for selecting effective pre-flush treatments to maximize CO₂ solubility and ensure long-term storage security.

2 Saline Aquifers

Saline aquifers are among the most promising geological formations for large-scale CO₂ storage due to their widespread global availability, high storage capacity, and hydrodynamic separation from freshwater resources [51, 52]. Their high porosity and permeability facilitate the injection and migration of CO₂, while overlying impermeable caprocks (such as shale or mudstone) act as effective seals to trap the gas

and prevent upward migration [11].

The global storage capacity of deep saline aquifers is estimated to be thousands of gigatons, significantly higher than that of depleted oil and gas fields or coal seams [12]. Furthermore, their wide geographic distribution allows CO₂ sources to be matched with nearby storage sites, reducing transportation needs. Operational projects such as Sleipner in the Utsira Sand formation (Section 1) have contributed significantly to understanding CO₂ plume behavior, geochemical interactions, and long-term containment mechanisms [15].

2.1 High Storage Capacity and Global Availability

Saline aquifers are expected to hold the largest CO₂ storage potential globally, far exceeding that of depleted oil and gas reservoirs or unmineable coal seams. Their theoretical capacity is measured in thousands of gigatons, sufficient to accommodate centuries of CO₂ emissions at current rates [53]. Moreover, these formations are spread worldwide, including regions where large stationary CO₂ sources are located, minimizing the need for long-distance transport [10]. Two techniques have been established so far to evaluate aquifer storage capacity, namely regional aquifer-based and structural trap-based

assessments [54]. The widespread availability of saline aquifers facilitates geographically distributed deployment of CCS. Their geological location also allows integration into existing energy infrastructure. Consequently, they form a key support to global strategies aiming to mitigate climate change through emissions reduction [13]. Some saline aquifers currently in operation and potential CO₂ storage sites are described in Table 1, along with their geographical description.

2.2 Suitable Geological Conditions for Supercritical CO₂

For effective and secure storage, CO₂ must be injected at depths exceeding 800 m to achieve a supercritical state. In this state, CO₂ exhibits properties of both gases and liquids—high density and low viscosity—which enhance both injectivity and storage capacity. At supercritical conditions, CO₂ occupies less volume and migrates more predictably through porous media [17]. Most deep sedimentary formations provide the necessary temperature and pressure conditions to support supercritical CO₂. Furthermore, storing CO₂ in this state reduces the buoyancy force that drives migration upward, improving containment under caprock layers. These thermodynamic benefits make deep saline aquifers particularly suitable for long-term geological sequestration [13].

Thermal conditions are equally important. Temperature typically increases by 25–35 °C per km, meaning most deep sedimentary basins naturally support supercritical CO₂ at depths of 0.8–1.2 km. Reservoirs located in tectonically active or geothermal regions may reach these conditions at shallower depths, whereas cooler basins may require deeper injection. The coupling of pressure and temperature also affects CO₂ density, which in turn governs buoyancy forces and plume migration rates. Higher reservoir pressures promote greater CO₂ dissolution into brine, lowering the risk of upward migration and facilitating solubility and mineral trapping [55].

Therefore, selecting an injection depth that ensures stable supercritical behavior while maintaining a safe pressure margin below the fracture threshold is critical for both operational efficiency and long-term storage security. Proper understanding of these pressure-temperature relationships allows accurate prediction of plume evolution, reservoir capacity, and the extent of solubility and mineral trapping during geological sequestration [56].

In deep sedimentary saline aquifers, formation-pressure gradients are commonly close to hydrostatic conditions. Representative literature-based values are approximately 9.0–10.0 MPa/km (1305–1450 psi/km), while reported minimum horizontal stress gradients are approximately 12.0–17.0 MPa/km (1740–2465 psi/km) [13]. These values are screening ranges compiled for deep sedimentary basins and should not be interpreted as universal values for all storage formations. They are most relevant to brine-filled sandstone or carbonate reservoirs at depths sufficient to maintain dense or supercritical CO₂ conditions, typically approximately 0.8–2.0 km, although the applicable range varies with basin temperature, lithology, stress regime, pore-fluid pressure, and burial history. Because they are literature-derived regional ranges rather than measurements from a single field or well, basin-specific pressure and stress data should be used when these values are applied to a particular storage site.

The difference between formation pressure and minimum horizontal stress provides only an initial screening indication of the available pressure margin. The actual allowable injection pressure must be determined from site-specific geomechanical and flow analysis. It is affected by capillary pressure and multiphase pressure losses, near-wellbore skin and permeability, wellbore and completion integrity, caprock strength and sealing capacity, fault orientation and reactivation tendency, reservoir heterogeneity, and pressure interference between wells. In addition, the minimum horizontal stress is not necessarily equal to the fracture pressure; fracture initiation depends on the complete in-situ stress state, rock strength, pore pressure, well trajectory, and perforation geometry [57]. Consequently, injection pressure should remain below a site-specific pressure limit established through pressure-transient analysis, well-integrity assessment, geomechanical modeling, and fault-stability evaluation rather than being selected solely from regional gradient ranges.

2.3 Rock Characteristics

Porosity and permeability are critical physical attributes that define the storage and flow capacity of aquifers. Porosity, typically ranging from 10% to 30% in sandstone aquifers and 5% to 25% in carbonate aquifers, determines the amount of CO₂ that can be stored [58]. Permeability, which may vary from

tens to thousands of millidarcies, controls how easily CO₂ can be injected and spread within the reservoir. Higher permeability facilitates higher injection rates, reducing the number of wells and associated infrastructure [59]. The heterogeneity in these parameters, especially layering and anisotropy arising from formation lithology, affects plume movement and residual trapping efficiency. Understanding these properties through site characterization and modeling is essential to designing and operating successful CCS projects [10].

However, these characteristics are only averages that downplay heterogeneity, which necessitates site-specific assessment [60]. Thin and low-permeability interlayers within the saline aquifer act as barriers to CO₂ migration, restricting its vertical and lateral spread in the formation and complicating accurate estimation of storage capacity [58]. Moreover, the porosity-permeability relationship could vary over time due to geochemical reactions from CO₂-brine-rock interactions. For example, salt precipitation can reduce permeability by up to 35% with only a slight change in porosity, while in other cases, permeability might unexpectedly increase due to mineral dissolution [27]. Such phenomena highlight the importance of modeling and empirical studies that cover anisotropy, layered heterogeneity, and evolving rock-fluid interactions to accurately predict injectivity, storage efficacy, and long-term integrity of storage projects [50].

2.4 Trapping Mechanism and Long-Term Stability

Saline aquifers provide several mechanisms to trap injected CO₂, enhancing both storage security and longevity. These include structural and stratigraphic trapping beneath impermeable caprocks, residual trapping due to capillary forces, solubility trapping as CO₂ dissolves into formation brine, and mineral trapping through geochemical reactions [17, 61]. While structural trapping provides immediate containment, solubility and mineral trapping offer long-term stabilization. Over time, CO₂ dissolves into brine, reducing its buoyancy and mobility, while reactions with formation minerals lead to precipitation of stable carbonates. These processes are particularly important in heterogeneous reservoirs where plume migration can be complex due to various interplaying forces. The presence of multiple trapping mechanisms is a major advantage of saline aquifers [13]. In addition to these trapping mechanisms, CO₂-rock geochemical interactions within the reservoir and

at the caprock interface play a significant role in long-term containment security; such reactions alter porosity, permeability, and mineralogy over geological time scales, and their cumulative impact on storage integrity has been systematically reviewed for sedimentary rock systems [62]. The effectiveness of each trapping mechanism varies based on the geological and operational parameters of the aquifer, as summarized in Table 2, where the storage security is described over time, resulting from the factors responsible for storing CO₂.

Table 2. Comparison of CO₂ trapping mechanisms [51].

Mechanism	Effectiveness	Stability and timescale	Key influencing factors
Structural trapping	High	High, immediate to long-term	Caprock integrity, fault presence
Residual trapping	Moderate	High, short- to medium-term	Pore throat size, CO ₂ injection rate
Solubility trapping	Moderate	Very high, medium- to long-term	Water salinity, temperature
Mineral trapping	Low to moderate	Very high, long-term	Reactive mineral content, pH

CO₂ in deep saline aquifers is subjected to a spectrum of trapping mechanisms that evolve over different time periods. Initially, structural and stratigraphic trapping, accompanied by impermeable caprocks and sealing faults, immobilizes the CO₂ plume and prevents buoyant migration [19]. Simultaneously, residual or capillary trapping begins to restrict CO₂ as disconnected droplets inside the complex pore network, which is influenced by the reservoir's wettability and pore-scale heterogeneity [18]. As time passes, residual trapping often becomes more dominant than solubility trapping, as the amount of residually trapped CO₂ may exceed twice the dissolved amount after several decades [63]. This shift is further regulated by temperature, pressure, aquifer thickness, and injection strategies, as thicker and high-pressure formations exhibit higher residual trapping during the post-injection period.

Solubility trapping reduces the buoyant tendency of CO₂ by dissolution in brine, resulting in increased fluid density and improved convective mixing. However, its efficiency is strongly dependent on brine salinity and composition [17]. High salinity can critically limit solubility trapping, which ultimately hinders the

transition to mineral trapping [21]. Although a slow process, mineralization plays a strategic role in the long term.

Importantly, solubility trapping directly sets the stage for mineral trapping. The more CO₂ that dissolves, the more carbonic acid is available to react with formation minerals such as Ca-, Mg-, and Fe-bearing silicates and carbonates. Thus, optimizing CO₂ solubility in the short term will accelerate carbonate mineralization in the long term, leading to more effective CO₂ storage by coupling the two mechanisms [64, 65]. Figure 1 shows a simple schematic of how trapping mechanisms are involved in immobilizing CO₂, starting from the less stable and temporary structural trapping prone to buoyant migration, to a more permanent form of trapping by mineralization.




Figure 1. Contribution of different trapping mechanisms and permanency of storage.

The trapping mechanisms summarized in Table 2 apply broadly to both sandstone and carbonate saline aquifers; however, their relative significance varies with lithology. In sandstone formations, characterized by higher porosity, permeability, and mineral homogeneity, residual and solubility trapping dominate due to uniform pore connectivity and efficient CO₂-brine interaction [66]. Mineral trapping

in such systems is slow due to the limited reactive mineral content. In contrast, carbonate formations exhibit greater geochemical reactivity, with abundant Ca- and Mg-bearing minerals promoting faster carbonate reactions once CO₂ dissolves, although heterogeneity and fracture-dominated flow can reduce residual trapping efficiency [67].

3 Factors Affecting CO₂ Solubility and Injectivity in Saline Aquifers

The impact of temperature, pressure, pH, and brine salinity on CO₂ solubility is crucial to predict and model the dissolution and precipitation of minerals, as these factors significantly influence the CO₂ sequestration processes [68, 69]. For example, an increase in pressure leads to greater CO₂ dissolution within brine, which then produces carbonic acid and triggers mineral breakdown [28]. Also, mineral dissolution takes place because of CO₂-induced pH variations, which alter the balance between precipitation and dissolution reactions [64, 67, 70]. Therefore, a fundamental understanding of these interdependent forces is necessary for developing CO₂ storage techniques within saline aquifers [71]. The study of these factors is essential to develop the most effective CO₂ storage project while incorporating enhanced measures to improve storage efficiency.

3.1 Effect of pH

Formation brine reacts with CO₂ to produce weak carbonic acid, lowering the pH of the system. In most deep saline aquifers, the original formation brine exhibits a near-neutral to slightly alkaline pH, depending on mineralogy and ionic composition [17]. This baseline arises from carbonate buffering reactions involving dissolved bicarbonate and hydroxide ions, which maintain near-neutral conditions before CO₂ injection [51, 70]. The acidic environment created by CO₂ dissolution allows carbonate minerals to dissolve, which results in greater formation porosity. In contrast, CO₂ exsolves during depressurization, which leads to an increased pH, resulting in carbonate mineral precipitation and a decrease in formation porosity and permeability [28]. The movement of injected gas affects how CO₂ dissolves and evolves from water, which modifies geochemical reactions. Figure 2 depicts a pore-to-reservoir scale schematic of CO₂ and mineral dissolution with and without depressurization [28]. Pressure strongly governs pH evolution within the aquifer. At high pressures, CO₂ remains dissolved as carbonic acid, creating acidic conditions that enhance mineral dissolution. In the




Figure 2. State of CO₂ after injection, undergoing geochemical activity, and the impact of pressure on trapping: (A) CO₂ without depressurization and (B) evolution with depressurization (modified from [28]).

event of leakage or abnormal depressurization of the aquifer system, CO₂ expands and exsolves from the aqueous phase [72]. Through this evolution, the chemical equilibrium between CO₂ and minerals is re-established, leading to an increase in pH and precipitation of minerals. Such geochemical reaction shifts result in variations of reservoir characteristics, such as porosity and permeability [28].

A study utilizing data from the upper Mt. Simon sandstone at the Illinois Basin-Decatur Project (IBDP) demonstrated this pH evolution through numerical reactive transport simulations [73]. The reported pH values were predicted by coupled geochemical and flow models that account for CO₂ dissolution, carbonic acid formation, and mineral equilibrium reactions, rather than measured directly in the wellbore. According to these models, the initial pH of 5.87 was predicted to drop rapidly to 4.45 following CO₂ injection and to 4.13 after 10 years of simulation, with the pH change confined to within approximately 100 m of the wellbore. This region is the most prone to CO₂-induced dry-out, which implies a coupled impact of pH on mineral dissolution and salt precipitation upon CO₂ introduction. Several studies indicate that low pH is responsible for greater calcite dissolution in unsaturated zones, and it is the major

factor controlling the extent of calcite precipitation during CO₂ mineralization [51]. The variation in porosity and permeability due to CO₂ interaction is also limited to the regions where pH alteration took place [73].

3.2 Effect of Salinity

Formation brine containing high salt concentrations may promote salt precipitation in CO₂ injection zones, especially when the area near injection wells dries out. The reduction in formation porosity and permeability caused by salt precipitation negatively affects CO₂ injectivity. Salt precipitation risks can be reduced through freshwater pre-flush treatments that reduce the salinity of the brine, thus decreasing the chance of salt deposits [26]. Salinity significantly affects the solubility of CO₂ in brine. Typically, NaCl is the main salt present in saline aquifers, accounting for 70-90% of dissolved solids [74]. Because NaCl dominates the dissolved-salt inventory, it contributes most of the overall salting-out effect, although on an equal-molality basis divalent chlorides such as CaCl₂ and MgCl₂ impose a comparable or stronger salting-out effect owing to their higher ionic strength [69, 75]. At a microscopic level, this salting-out effect occurs because water molecules are highly polar and are strongly attracted to dissolved




Figure 3. CO₂ solubility in 1000 ppm brines at (A) 25 °C, (B) 60 °C, (C) 80 °C, and (D) 100 °C, plotted from data reported in [76].

Na⁺ and Cl⁻ ions, forming tight hydration shells. Because many water molecules are occupied by these strong ion-dipole interactions, fewer “free” water molecules are available to interact with and accommodate the non-polar CO₂ molecules. As a result, CO₂ is effectively pushed out of the aqueous phase, significantly lowering its solubility. In addition, Ca²⁺, Mg²⁺, and anions such as SO₄²⁻ alter activity coefficients and promote carbonate precipitation once CO₂ dissolves. Higher ionic concentrations further suppress solubility due to increased ionic strength [74, 76]. This is correlated with the different solubility trends shown in Figure 3, where the solubility of CO₂ in various ionic solutions of NaCl, CaCl₂, MgCl₂, and MgCl₂+CaCl₂ was determined at different temperature and pressure conditions. As observed, the solubility of CO₂ increased at higher pressures and decreased at higher temperatures. The experiments used a relatively low total salt concentration of 1000 ppm; therefore, these data are most representative of dilute brines and should not be directly extrapolated to highly saline storage formations [76].

Formation brine compositions are extremely important when mimicking aquifer conditions at the laboratory scale, as they dictate the extent and rate at which CO₂ dissolves in the brine [77]. It is important to note that brine concentration generally increases with reservoir

depth [78]. Considering realistic salinity values while preparing brines is essential for designing conditioning treatments that achieve realistic and efficient results at the field level towards increasing CO₂ storage capacity. High salinity not only suppresses solubility but also delays the onset of mineral trapping by limiting the dissolved CO₂ available for geochemical reactions. Pre-flush methods that lower salinity can therefore enhance both solubility and the subsequent precipitation of stable carbonates.

3.3 Effect of Temperature and Pressure

Temperature and pressure play crucial roles in CO₂ sequestration by altering CO₂ solubility. These two parameters go hand in hand, and their effects are usually interdependent [79]. An elevated-pressure environment allows brine to absorb more CO₂ molecules, which transform into carbonic acid that dissolves rock minerals and enlarges pore spaces. Low formation pressure causes CO₂ to exsolve, which results in increased pH and the formation of carbonate deposits that diminish permeability [28].

Increased temperatures cause brine to become less accommodating of CO₂ molecules, thus hindering carbonic acid formation and reducing mineral dissolution rates. At higher temperatures, CO₂ solubility decreases because molecular kinetic

energy increases, reducing gas dissolution potential. Optimal conditions for solubility occur at high pressures (10-20 MPa) and low temperatures (below approximately 310 K, or 37 °C), as shown in Figure 3. Conversely, low pressures and high temperatures yield minimum solubility. Temperature elevation accelerates reaction rates, which may boost mineral dissolution and precipitation tendencies depending on the specific geochemical characteristics of the area [70]. Effective storage in saline aquifers requires a moderate range of subsurface temperature and pressure to preserve both injection rates and long-term stability. Deng et al. [80] determined CO₂ solubility in deionized (DI) water and two kinds of formation brine as a function of temperature and pressure.

Solubility rises with increasing pressure but decreases with higher temperature and salinity. The highest solubilization occurs in low-salinity or deionized water under high-pressure and low-temperature conditions, while solubility is most limited in concentrated brines at elevated temperatures and low pressures [80]. Comparable trends were observed in CaCl₂ and MgCl₂ systems, where solubility decreased with temperature, and differences relative to NaCl solutions were attributed to differences in ionic strength [75].

4 Pre-flush Treatment to Improve CO₂ Solubility

Efforts to enhance CO₂ solubility trapping revolve around conditioning the aquifer and increasing the contact between CO₂ and brine to speed up dissolution, and improving the capacity of the brine to hold CO₂ by altering its composition or the CO₂ phase behavior [81]. Pre-flush treatments refer to injecting a fluid or additive into the formation either before CO₂ injection (pre-flush) or alongside/after CO₂ injection (sometimes in cycles), to promote CO₂ dissolution and maintain injectivity [26]. This paper discusses several categories of conditioning treatment in the following sections, including injecting freshwater, low-salinity water, chelating agents, surfactants, and nanoparticles [82, 83].

4.1 Freshwater and Low-salinity Water Injection

Because high salinity is a major factor limiting CO₂ solubility, a logical technique is to inject low-salinity water into the aquifer before CO₂ injection to locally dilute the brine. By pushing out or diluting the brine around the injection zone, the CO₂ will first contact a fresh/low-salinity water phase, where it can dissolve more readily [30]. This strategy also has an immediate

practical benefit, as it mitigates salt precipitation. LoSal water injection has previously been implemented to resolve halite formation issues near the wellbore and in the tubing of gas-producing wells [33]. When dry CO₂ is injected into saline aquifers, it tends to dry out the near-wellbore brine by evaporation, potentially precipitating salt and clogging pores. Freshwater washing was also used in the Quest CCS project to remediate halite deposition in CO₂ injection wells, where it improved CO₂ injectivity by up to 263% [32].

The main strength of this approach is its simplicity and strong mechanistic basis. Simulation studies and field experience consistently indicate that maintaining a less saline, water-rich near-wellbore region delays permeability loss and pressure build-up during CO₂ injection [26]. Compared with chemically more complex options, freshwater pre-flush does not depend on interfacial formulation stability or complex reaction pathways. It also integrates naturally with injectivity management because the same treatment that suppresses salt precipitation can increase the fraction of CO₂ entering the dissolved phase. In addition, lower salinity can promote convective mixing and improve the transition from structural or mobile CO₂ to more stable dissolved and residually trapped phases. For these reasons, freshwater or engineered low-salinity injection is generally the most field-ready option for reservoirs where salt precipitation is the dominant near-wellbore risk [31].

In field applications, a low-salinity pre-flush could be implemented by diverting some produced water (if of low salinity) or treated seawater into the injection well before starting CO₂ injection. Additionally, injecting freshwater before CO₂ helps remedy permeability loss and salt precipitation [25]. It was further proposed to add 3% butyl glycol to freshwater to eliminate halite precipitation in wells, although with unsatisfactory results [33]. Figures 4 and 5 compare the simulated salt concentration profiles for dry CO₂ injection without and with a freshwater pre-flush, respectively [25]: the pre-flush lowers and delays the development of the salt-saturated zone near the wellbore, although a saturated zone still develops after prolonged injection. Alternatively, co-injecting water vapour (steam) with CO₂ to keep the near-wellbore region humidified has been considered, but the energy required for compression and heating imposes significant environmental and economic penalties.

Beyond injectivity and dissolution, freshwater or low-salinity water injection plays a role in modifying




Figure 4. Salt concentration profile versus distance from the borehole after dry CO₂ injection without pre-flush (reproduced from [25]).




Figure 5. Salt concentration profile versus distance from the borehole after dry CO₂ injection following a freshwater pre-flush (reproduced from [25]).

the movement, mixing, and stabilization of CO₂ plumes. Because CO₂ is more soluble in low-salinity brine, a larger dissolved-CO₂ load produces a greater density increase relative to the ambient brine, thereby amplifying density-driven convective mixing and further enhancing the rate of CO₂ dissolution into the aqueous phase [71, 84]. Freshwater slugs also mitigate capillary end effects near the injection well. By sustaining water saturation, they suppress the development of dry-out zones where evaporative salt precipitation occurs [26, 50]. Hence, permeability is preserved and residual trapping is enhanced, as the retained water phase ensures CO₂ becomes immobilized as disconnected ganglia [63, 66]. Despite its ability to dilute formation brine and reduce salt precipitation, low-salinity water injection may introduce formation-damage

risks in clay-bearing or fines-sensitive aquifers. A sudden reduction in ionic strength can increase the diffuse double-layer thickness around clay particles, promote clay swelling or dispersion, and weaken particle attachment to mineral surfaces. Mobilized fines may subsequently migrate and accumulate at pore throats, causing permeability reduction and injectivity impairment. The magnitude of this response depends on clay mineralogy and content, the initial brine composition, the concentration of divalent ions, pH, salinity contrast, injection rate, and the spatial distribution of low-permeability layers. Therefore, low-salinity pre-flushing should not be considered universally beneficial; the salinity and ionic composition of the injected water should be selected to minimize salt precipitation while maintaining rock-fluid compatibility. Site-specific compatibility tests, including coreflood experiments, effluent turbidity or particle analysis, permeability monitoring, and mineralogical characterization, are required before field application.

Importantly, freshwater and LoSal water conditioning can accelerate the transition from solubility trapping to mineral trapping. As more CO₂ dissolves, carbonic acid generation increases, promoting carbonate precipitation with divalent cations in the aquifer [20, 21]. In systems rich in reactive minerals such as feldspars or carbonates, this coupled process significantly boosts long-term storage security.

4.2 Chelating Agents

In recent years, the use of chelating agents to extract magnesium or calcium ions from silicate minerals to enhance mineral carbonation has been studied [36]. The injection of biodegradable chelating agents such as GLDA with seawater was found to be effective in improving rock porosity by dissolving surface-bound Ca²⁺ and Mg²⁺, which enlarges pore throats and improves flow connectivity. GLDA also led to an increase in mineral dissolution, enhancing the permeability and connectivity of pores for better CO₂ injectivity [35]. Owing to their ability to bind cations over a wide range of pH values, their use has extended to the extraction of these cations for industrial purposes and CO₂ mineralization. For instance, EDTA significantly enhances the extraction of Mg from serpentine, an Mg-rich mineral [85]. Moreover, GLDA-based fluids dissolve carbonate rock in a controlled manner at elevated temperatures, and their dissolution rate and wormholing behavior can be tuned through concentration and pH, which makes

it possible to balance acid-driven dissolution against secondary carbonate precipitation [86]. However, the efficiency of a ligand depends on its concentration and on the stability constant of the complex it forms with the target metal. For example, controlling CaCO_3 precipitation requires an appropriate chelant concentration and complex stability. For this case, at 25 °C and 0.1 M ionic strength, the stability constants ($\log K$) of the Ca-EDTA and Ca-GLDA complexes are 10.7 and 5.9, respectively [34, 87]. The higher the stability constant, the more strongly the ligand binds the metal ion [88]. However, to maintain rigor in the context of geological carbon storage, it is critical to account for actual subsurface conditions. Deep saline aquifers typically present much harsher environments, characterized by elevated temperatures (often 50-100 °C) and highly concentrated formation brines with ionic strengths far exceeding 0.1 M. Under these elevated reservoir temperatures and high-salinity conditions, the thermodynamic stability constants and overall binding affinities of these chelating agents will shift, generally reducing their effective chelating capacity. Consequently, the design of chemical pre-flush strategies must be carefully tailored to the specific environmental conditions of the target aquifer. In Figure 6, the working of GLDA as a biodegradable chelating agent is graphically depicted, explaining the steps from injection to carbonate mineralization.

It is crucial to consider the cation when choosing a chelating agent, as the stability of the chelated species depends on metal-ion properties. The greater the charge of the ion, the more stable the complex it forms with the chelating agent [89]. The potential to form complexes is determined by the charge and radius of the binding metal at the appropriate pH, as explained by Martell and Calvin [90]. Stability increases with z^2/r , where z is the ionic charge number and r is the ionic radius. The presence of d-orbitals is also crucial for the formation of stable coordination complexes, as transition metals are more likely to form chelate complexes [91]. For example, EDTA forms stable complexes with Ca^{2+} and Mg^{2+} , but Na^+ , being a monovalent cation with a single charge and weak electrostatic attraction, forms complexes of negligible stability with EDTA in solution. Moreover, chelating agents tend to form multiple bonds with a metal ion, which is possible only with multivalent cations. Therefore, chelating agents are preferred for extracting multivalent rather than monovalent cations [91]. The coordination chemistry of the binding chelant is crucial in treating different cations. Table 3 lists the

stability constants of selected EDTA-metal complexes to indicate the binding strength of the ligand.

Table 3. Stability constants of selected cations with EDTA (25 °C, $I = 0.1$ M) [87].

Cation	Stability constant ($\log K$)
Fe^{3+}	25.1
Cu^{2+}	18.8
Ni^{2+}	18.6
Pb^{2+}	18.0
Zn^{2+}	16.5
Co^{2+}	16.3
Ca^{2+}	10.7
Mg^{2+}	8.7
Na^+	1.67
K^+	1.33

Alternatively, the ionic strength of the injected fluid must be carefully managed in clay-bearing formations. When the salinity of the conditioning fluid drops below a critical threshold—as may occur during chelant-assisted or low-salinity pre-flush operations—clay fines near the injection well can detach from grain surfaces, migrate through pore throats, and cause significant permeability decline and injectivity impairment [92]. This risk is further amplified in formations with high clay content or poorly cemented grains, where even moderate salinity reductions can initiate fines detachment and pore-throat plugging, underscoring the need for careful ionic-strength management during any pre-flush operation. Chelating agents also play a crucial role in accelerating mineral trapping. By releasing Ca^{2+} and Mg^{2+} from silicates and carbonates, chelants increase the availability of reactive cations that precipitate as calcite or magnesite once CO_2 dissolves [20, 21]. For instance, wollastonite dissolution was reported to be enhanced by chelating agents, leading to faster carbonate formation [36]. Other industrially available chelating agents are nitrilotriacetic acid (NTA) and diethylenetriaminepentaacetic acid (DTPA) [36].

However, challenges remain. High concentrations are needed for effectiveness, raising cost and environmental risks [93]. Chelants may mobilize trace metals and degrade under high salinity or temperature [89]. Field use has been limited to wellbore cleanouts rather than reservoir-scale deployment [94]. Future directions include green chelants such as GLDA that are biodegradable and effective under variable pH, and combining chelants with low-salinity injection to balance solubility and




Figure 6. Mechanism of GLDA as a biodegradable chelating agent in CO₂ sequestration: (1) injection of GLDA to extract metal ions, (2) CO₂ dissolution and acidification, and (3) carbonate mineralization with GLDA biodegradation (reproduced from [35]).

mineralization [35]. These integrated approaches could bridge short-term injectivity improvements with long-term carbonate stability.

4.3 Nanoparticle-based CO₂ Injection

Nanoparticles (NPs) have emerged as a powerful tool in subsurface engineering due to their ability to modify fluid-fluid and fluid-rock interactions at the pore scale. For CO₂ sequestration, NPs can be used to stabilize CO₂-in-brine emulsions or foams, enhance convective mixing, and alter interfacial forces, all of which contribute to increased solubility trapping. Specifically, NP-stabilized foams, also known as Pickering foams, can disperse CO₂ into fine bubbles within brine, dramatically increasing the gas-liquid interfacial area and thus accelerating dissolution [37, 38].

Nanoparticle-based approaches have been investigated primarily as interfacial and mobility-control strategies rather than as direct chemical solubility enhancers. Across the available studies, their main contribution

is to improve CO₂-brine contact by stabilizing foams, modifying wettability, and, in some cases, increasing the density contrast that promotes convective mixing [37, 38, 95]. Silica-based nanoparticles are the most consistently studied and appear to be the most practical because they can stabilize CO₂ foams under harsh salinity and temperature conditions, reduce gas mobility, and prolong gas residence time in the aqueous environment, thereby increasing the opportunity for dissolution [37]. More broadly, nanoparticle-stabilized foams have been shown to improve sweep efficiency, suppress viscous fingering, and produce more uniform displacement fronts than CO₂ injection alone, indicating that their storage benefit arises mainly from hydrodynamic control and interfacial stabilization rather than from a direct increase in intrinsic CO₂ solubility [38].

The literature also suggests that nanoparticle performance depends strongly on particle type and intended mechanism. High-density or heavy-metal

nanoparticles (such as Pb, UO_2 , and steel) have been proposed as a means of accelerating convective mixing by increasing the density of the CO_2 -rich phase. However, these must be strictly classified as theoretical exploration models. Owing to severe environmental toxicity and leakage-related concerns, they are not applicable to actual saline aquifer engineering. Such concepts remain purely theoretical and are far less practical than silica-based foam stabilization, which avoids these severe environmental and injectivity concerns [95]. In contrast, surfactant-nanoparticle systems appear more promising for storage applications because they combine foam stability with wettability alteration, often shifting the rock toward a more water-wet state and thereby improving capillary trapping in addition to dissolution [38, 66]. Overall, the comparative evidence indicates that nanoparticles are most valuable as supporting additives in mobility-control formulations, especially foam systems, whereas their direct use as standalone injectants remains less mature and less suitable for near-term field deployment [37, 38].

Recent advances employ surface-functionalized nanoparticles—for example, mesoporous silica or metal oxide NPs grafted with functional groups—to improve dispersion, reduce aggregation, and enhance interfacial stability under high salinity and temperature conditions (e.g., ethoxylated coatings, silane-modified surfaces) [96]. These tailored NPs serve as superior foam stabilizers in CO_2 -brine mixtures, increasing interfacial elasticity, resisting coalescence, and extending foam life under harsh reservoir conditions [97]. Purification and redispersion techniques, such as solvent-free washing and supercritical CO_2 drying, have been explored to maintain NP stability after preparation, which is essential to preserve performance at injection scales [98].

Another emerging approach is combining NPs with nanobubbles, leveraging their synergistic effect on CO_2 dissolution and transport. Nanobubbles remain dispersed longer and increase the CO_2 -brine contact area, while NPs assist in stabilizing bubble interfaces and enhancing mixing [39, 99]. Some preliminary modeling and laboratory results suggest that such hybrids can significantly enhance dissolution rates beyond what NPs or bubbles alone achieve. Importantly, NP-stabilized foams retained stability over several hours of injection and demonstrated the ability to reform after pressure cycling, a key

requirement for field-scale efficiency [38].

Complementing experimental work, a comprehensive theoretical review and modeling study of nano-modified CO_2 injection was carried out by Rathnaweera and Ranjith [39]. Their work proposed that adding nanoparticles directly into the CO_2 stream (nano- CO_2) could accelerate convective mixing by increasing the density and viscosity of the injected fluid, thus altering the Rayleigh number and reducing the onset time of convection. Based on model predictions tested across 32 saline aquifer case studies worldwide, they found that nano- CO_2 injection could reduce the convective onset time by up to 80% and improve solubility trapping by around 50% relative to conventional CO_2 injection. They also highlighted that nanoparticles improve interfacial tension behavior, modify wettability, and minimize CO_2 mobility, which jointly enhance the stability and storage capacity of CO_2 in deep saline formations.

Despite these advantages, NP deployment faces hurdles: aggregation risks, injectivity concerns, high costs, and environmental compatibility [38, 100]. These limitations may become more significant during scale-up because heterogeneous formations can cause uneven nanoparticle transport and preferential accumulation in high-permeability channels or near-wellbore regions. Therefore, the improved foam stability observed in laboratory cores may not translate into uniform mobility control over field-scale distances. To date, no CCS project has applied NPs at the field scale, and the uncertainty associated with reservoir heterogeneity, fluid fingering, and long-distance additive transport remains a major barrier to field deployment. In terms of mineral trapping, NPs indirectly accelerate carbonation by maximizing dissolved CO_2 availability. Some metal oxide NPs (e.g., MgO , CaO) may even directly participate in carbonate formation under reservoir conditions, though this remains experimental [101].

4.4 Surfactant and CO_2 -foam Injection

The use of surfactants to create CO_2 foams is a well-established technique in enhanced oil recovery. Foam reduces CO_2 mobility by forming a dispersion of gas within the aqueous phase, stabilized by surfactant molecules at the gas-liquid interface, and enhances solubility and residual trapping of CO_2 by extending residence time, increasing the gas-brine contact area, and distributing the CO_2 more uniformly through the formation. This reduction in mobility addresses a major challenge of supercritical CO_2 : its tendency to

Table 4. Selected surfactants and their implications for CO₂ storage efficiency.

References	Surfactant	Main contribution	Key limitations
[102, 103]	Zwitterionic betaine (e.g., cetyl betaine)	Forms stable CO ₂ foams at high temperature (≤ 150 °C) and salinity (≤ 22 wt% TDS); improves mobility control and sweep efficiency.	Higher dosage may be required because of adsorption and partitioning losses; cloud-point precipitation and mineral adsorption may reduce propagation distance.
[104]	Nonionic ethoxylates (e.g., C ₁₂₋₁₄ (EO) ₂₂)	Maintain foam stability at high temperature and salinity owing to a high cloud point; enhance in situ foam generation.	Require higher dosage; cloud-point precipitation risk; adsorption on minerals.
[40, 105]	CO ₂ -soluble surfactants (e.g., ethoxylated amines, CO ₂ -philic nonionics)	Generate foam in situ through the CO ₂ phase; reduce mobility and improve sweep in carbonates.	Partitioning and adsorption losses can reduce surfactant concentration along the flow path; limited solubility in supercritical CO ₂ ; possible handling or environmental concerns.
[38, 106]	NP + surfactant hybrids (e.g., silica NP + betaine/SDS)	Reinforced interfacial films give long-lived foams; enhance CO ₂ dissolution and residual trapping.	Divalent-ion sensitivity, adsorption and retention on mineral surfaces, dispersion instability, and possible injectivity impairment at field scale.

finger through brine and bypass large swathes of the formation due to its low viscosity and density.

Surfactant-based CO₂ foams are increasingly viewed as one of the most practical chemical strategies for improving storage performance in saline aquifers because they address a limitation that freshwater or chelating treatments do not directly solve: unfavorable CO₂ mobility. Across the reported studies, the main advantage of foam systems is their ability to redistribute CO₂ more uniformly, improve sweep efficiency, and increase gas-brine contact time, thereby enhancing both residual and solubility trapping [41, 42]. The literature also shows that foam effectiveness is not determined by surfactant presence alone, but by formulation quality, phase partitioning, and the ability to maintain foam strength under reservoir salinity, temperature, and heterogeneity.

A consistent finding across these studies is that stronger storage performance is obtained when foam propagation is balanced with injectivity and stability. High-dryness (ultralow water content) foam systems can provide strong plugging and mobility reduction, leading to deeper and more uniform sweep while lowering water consumption relative to conventional aqueous foam injection [103]. At the same time, comparative core-flood studies show that surfactant partitioning behavior is a critical design variable, since formulations that partition

appropriately between CO₂ and brine generate earlier and more persistent foam, whereas poor CO₂ solubility or excessive stripping reduces storage benefit and accelerates foam decay [41]. This indicates that surfactant performance should be evaluated not only by foam strength, but also by resistance to stripping, adsorption losses, and the sustainability of foam propagation over multiple pore volumes. The distinction between conventional aqueous-phase surfactants and CO₂-soluble surfactants is especially important from a review perspective. Conventional surfactants can provide substantial mobility control, but CO₂-soluble surfactants offer an additional advantage by generating foam directly at the CO₂-brine interface within the formation, which improves propagation under continuous CO₂ injection and reduces phase-segregation problems [42]. This appears particularly beneficial in carbonate, layered, or heterogeneous systems, where in situ foam generation can improve sweep while avoiding severe injectivity penalties. Overall, the comparative evidence suggests that surfactant-based foams are among the most mature options for saline aquifer conditioning, but their success depends strongly on selecting formulations with appropriate partitioning, salinity tolerance, thermal stability, and adsorption behavior rather than on maximizing foam strength alone [41, 42, 103].

Surfactant adsorption on reservoir minerals is an important factor governing the field-scale performance and economics of CO₂-foam injection. Carbonate surfaces and clay-rich minerals can retain surfactant molecules through electrostatic, hydrophobic, or surface-complexation interactions, thereby consuming part of the injected chemical before it reaches the displacement front. Consequently, the required surfactant dosage and injection volume may be higher than laboratory estimates, increasing chemical procurement, mixing, transportation, and pumping costs. Adsorption can also produce concentration attenuation along the flow path, causing foam generation and mobility control to weaken with distance from the injector and limiting the effective transmission distance of the foam bank. However, adsorption is not necessarily detrimental in all cases. The adsorbed surfactant layer may alter rock wettability and interfacial properties, potentially promoting a more water-wet condition and enhancing residual CO₂ trapping. The net effect depends on mineralogy, surfactant type, brine salinity, pH, temperature, and the reversibility of adsorption. At longer times, desorption, chemical degradation, and redistribution of the surfactant may reduce foam stability and cause spatially variable wettability effects. Therefore, adsorption capacity and retention should be incorporated into formulation design, coreflood testing, foam-transport modeling, and economic evaluation rather than being treated only as a chemical-loss mechanism. Table 4 lists some surfactants and CO₂ foams that assist in enhancing CO₂ storage efficiency by improving mobility control and sweep efficiency, while simultaneously increasing residence time for gas-liquid contact.

Among the tested nanoparticles, silica (SiO₂) and surface-functionalized metal oxides (such as MgO and CaO) have shown the most consistent performance in enhancing CO₂ solubility and foam stability under reservoir conditions. Their hydrophilic or modified surfaces promote strong interfacial activity, improved wettability toward water-wet states, and stable dispersion at high temperature and salinity [37, 38, 96]. In contrast, heavy-metal or dense nanoparticles such as Pb, UO₂, and steel, though theoretically beneficial for increasing convective mixing due to higher density, present environmental risks, aggregation issues, and injectivity challenges, making them less suitable for large-scale application [95, 100]. Overall, silica and surface-modified oxides are considered the most practical nanoparticle options for enhancing CO₂

storage efficiency in deep saline aquifers.

Hybrid systems combining surfactants with surface-modified NPs are gaining attention. The NPs reinforce the elastic modulus of the surfactant film and reduce drainage, yielding more stable CO₂ foams under reservoir salinities [107]. In particular, novel NP coatings tuned for interfacial affinity have improved foam stability over extended durations, potentially enabling deeper penetration and longer residence times [97]. This synergy opens a pathway where surfactant foams are reinforced by NP frameworks, enhancing dissolution while maintaining foam robustness in subsurface operations.

Limitations of CO₂ foams include adsorption losses on minerals, salinity sensitivity, and degradation risks [44]. Economic and environmental factors, especially for large-scale projects, require further validation [43]. Foams strongly couple solubility and mineral trapping. By dispersing CO₂, they increase dissolution, while the extended residence time enhances carbonate precipitation with reactive minerals [28]. This dual mechanism makes surfactant foams one of the most practical near-term pre-flush strategies.

4.5 Comparative Evaluation and Mineral Trapping Integration

The comparative assessment of pre-flush techniques shows that each method enhances CO₂ solubility through distinct mechanisms and under different reservoir conditions. Freshwater or low-salinity injection is the most direct approach and has been field-tested as a remedial wash [32], reducing brine salinity and preventing salt precipitation near the wellbore. It may improve injectivity by preventing halite deposition, but it may also reduce injectivity through clay swelling or fines mobilization. Its selection should be based on the balance between these competing mechanisms rather than on salt-precipitation control alone. Chelating agents improve injectivity and promote mineral trapping by binding multivalent cations, though their cost and stability limit large-scale use. Nanoparticles modify interfacial behavior and enhance CO₂-brine contact, while surfactant-based foams control CO₂ mobility and increase sweep efficiency.

Hybrid systems, such as nanoparticle-surfactant or chelant-assisted low-salinity injections, combine these benefits to improve both dissolution and mineralization. The performance of each technique

depends strongly on formation mineralogy; sandstones favor solubility and residual trapping, whereas carbonates enhance mineral trapping due to higher reactivity. Overall, selecting an appropriate pre-flush method requires balancing injectivity, dissolution, and chemical stability to achieve secure and efficient CO₂ storage. From an engineering perspective, surfactant adsorption creates a trade-off between immediate chemical consumption and possible long-term wettability modification. Strong adsorption may increase the initial chemical requirement and reduce the distance over which foam remains effective, but the retained surfactant can continue to influence rock wettability after the mobile surfactant concentration has declined. This may improve residual CO₂ trapping, although excessive retention or degradation can reduce foam regeneration and lead to non-uniform treatment. Accordingly, the economic assessment should consider not only the unit price of the surfactant, but also adsorption-induced dosage increases, repeat injection requirements, water and mixing requirements, injectivity effects, and the incremental cost per tonne of CO₂ stored.

Integration of pre-flush injection with mineral trapping. All of these methods can accelerate the progression from solubility to mineral trapping by increasing CO₂ dissolution and carbonic acid formation, thereby enhancing geochemical stability. Hybrid approaches such as NP-surfactant foams or chelants with LoSal slugs may offer the most efficient solutions, balancing short-term injectivity management with long-term storage security. While each pre-flush method enhances solubility through distinct mechanisms, their long-term value lies in how they accelerate mineral trapping. Greater dissolution increases the dissolved inorganic carbon content, which drives carbonate precipitation. Thus, solubility optimization should be viewed not only as a short-term injectivity or storage efficiency measure, but also as a direct catalyst for geochemical stabilization in saline aquifers.

4.5.1 Reservoir Heterogeneity and Scale-Up Uncertainty

Results from nanoparticle-assisted foam experiments should be interpreted cautiously when extrapolating from pore and core scales to field-scale CO₂ storage. Laboratory cores are commonly smaller, more homogeneous, and less structurally complex than reservoir formations. In contrast, saline aquifers may contain layered permeability contrasts, shale or clay-rich interbeds, natural fractures, anisotropy, variable porosity, and spatial changes in mineralogy and wettability. These features can divert the injected

CO₂-brine-additive mixture into preferential flow paths and create regions that are poorly contacted by the treatment. Consequently, the foam strength, nanoparticle distribution, and wettability alteration measured in a core may not be maintained uniformly over the much longer distance between an injection well and the reservoir volume.

Fluid fingering is an additional source of uncertainty during scale-up. Because CO₂ has a lower viscosity than brine and is affected by density differences, viscous fingering, gravity override, and channeling through high-permeability layers may occur. Foam can reduce these effects by increasing the apparent CO₂ mobility resistance; however, foam generation and stability may vary spatially because of surfactant adsorption, nanoparticle retention, salinity gradients, pressure changes, and local permeability. Fingering may therefore cause early breakthrough in preferential channels while leaving unswept or weakly treated regions between the channels. This reduces the effective transmission distance of the foam and introduces uncertainty in predictions of dissolution, residual trapping, and injectivity at the wellbore scale.

A rational scale-up methodology should therefore combine multiscale reservoir characterization with coupled flow and transport modeling. Relevant characterization includes core and log measurements of permeability, porosity, capillary pressure, mineralogy, fracture distribution, and wettability. These data can be incorporated into heterogeneous geostatistical models and evaluated using compositional foam-flow simulations that account for nanoparticle transport, adsorption, dispersion, retention, and foam collapse. Sensitivity analysis or ensemble simulations should then be used to quantify the effects of permeability contrast, layer thickness, fracture connectivity, injection rate, foam quality, and surfactant or nanoparticle concentration. Field pilots, tracer tests, pressure monitoring, and repeated coreflood experiments using heterogeneous or fractured cores would further reduce the uncertainty. Therefore, laboratory results should be regarded as evidence of mechanism and formulation performance, whereas reservoir-scale effectiveness requires validation through heterogeneous models and field-representative experiments.

5 Field Readiness and Application

Although freshwater or low-salinity pre-flushes are rarely documented in commercial CO₂ storage projects, modeling and experimental studies strongly

support their value in mitigating near-wellbore salt precipitation, a major risk to injectivity [26]. Numerical simulations indicate that pre-injecting a slug of freshwater before CO₂ can significantly reduce salt crystallization, preserving formation permeability during injection [25, 26]. These findings have been echoed in broader reviews, which show that salt deposition tends to cluster near the injection zone and can severely impair injectivity, even with minor porosity loss [29]. However, this method has not been implemented as a routine pre-flush in projects such as Sleipner, Snøhvit, or Aquistore. At Snøhvit, near-wellbore salt precipitation contributed to a rapid pressure build-up in the Tubåen Formation and required well interventions [108], illustrating the relevance of salt-related clogging and the potential value of pre-flush applications.

When it comes to chelating agents, nanoparticles, and surfactants, the field evidence remains sparse. Laboratory studies have demonstrated that chelants like EDTA can clean scale and prevent iron precipitation in wellbores, but these approaches are used primarily in oilfield maintenance, not in commercial saline aquifer storage [94]. Similarly, surfactants show potential: core-flood studies report that surfactants can increase CO₂ storage efficiency by helping generate foam or reducing interfacial tension, with improvements of up to 32% [109]. Yet, these remain confined to laboratory or simulation environments; their practicality at scale and compatibility with specific reservoirs are still being evaluated at the field level [43].

Finally, nanoparticles present an intriguing but still theoretical path forward. Some recent reviews argue that nanoparticle-augmented formulations (often combined with surfactants) may enhance CO₂ diffusivity, wettability control, and foam stabilization in harsh conditions, making them promising in concept for future field use [101]. Still, there have been no field CCS deployments of NP-based pre-flush or foam strategies. Interestingly, analogous trials in EOR contexts (such as nanoparticle-assisted CO₂ huff-n-puff pilots) have shown feasibility in oil recovery settings, but the relevance to CO₂ storage reservoirs remains to be demonstrated [100].

Lessons from field applications emphasize the need for cost optimization, particularly because adsorption losses may require additional surfactant volume or repeated treatment. The economic assessment should therefore include surfactant purchase, formulation

and mixing, transport, injection, produced-fluid or residual-chemical management, and the cost associated with possible injectivity impairment or remediation. A formulation with a higher unit price may still be economically preferable if it has low adsorption, propagates over a longer distance, and maintains foam stability for multiple pore volumes. Hence, the relevant metric is the incremental cost per tonne of CO₂ stored or immobilized, rather than the surfactant price alone. Optimizing slug size, concentration, injection sequence, and surfactant-nanoparticle composition can reduce chemical losses while maintaining the required sweep and trapping benefits. Table 5 compares the economic aspects of different pre-flush methods and lists the influencing parameters.

6 Current Challenges and Future Prospects

Despite encouraging laboratory results, pre-flush techniques for CO₂ storage face substantial challenges when translated into field applications. The most immediate limitation is injectivity risk; while freshwater or low-salinity pre-flushes can mitigate salt precipitation, they may simultaneously destabilize clays or mobilize fines, leading to permeability loss rather than improvement [112]. Similarly, the use of chelating agents such as EDTA or GLDA is constrained by cost, large volume requirements, and potential geochemical side-effects, including mobilization of trace metals or alteration of mineral equilibria [113]. Surfactant-based foams, although effective in laboratory porous media, remain sensitive to reservoir salinity, hardness, adsorption, heterogeneity, and fluid fingering [114]. These effects can cause non-uniform foam propagation and early CO₂ breakthrough, making the prediction of effective sweep distance and storage improvement uncertain at the wellbore and reservoir scales. Similarly, nanoparticle-surfactant foams require validation in heterogeneous and fractured media before their laboratory performance can be considered representative of field behavior [38].

Looking forward, prospects for pre-flush methods in CCS are promising but hinge on careful site-specific design and incremental field validation. One avenue is the adaptation of intermittent or slug-based pre-flushes, where small volumes of LoSal water or surfactant solution are co-injected with CO₂, minimizing risks of clay swelling while maintaining injectivity [29, 30]. These clay-related risks should be evaluated during the initial design stage because

Table 5. Cost evaluation of different pre-flush techniques and their cost drivers.

Method	Cost drivers	General cost range	Sources
Freshwater/low-salinity water injection	Pumping, sourcing, treatment, or desalination (especially offshore)	USD 0.5-1.5 per m ³ of treated seawater or desalinated water	[110, 111]
Chelating agents (EDTA, GLDA, NTA, DTPA, IDS)	Bulk chemical purchase, large dosages, possible degradation	USD 2-6 per kg (industrial grade); injection treatment typically requires several tonnes per well	[89, 94]
Nanoparticles (e.g., silica, metal oxides)	Synthesis, surface modification, stabilization, dispersion handling	USD 5-50 per kg (depending on NP type and purity)	[38, 39]
Surfactants/CO ₂ foams	Surfactant purchase, injection, adsorption losses	USD 2-10 per kg (anionic surfactants); CO ₂ -soluble or specialized surfactants can exceed USD 10 per kg	[40, 43, 45]

Table 6. Impact of geological formation type on chemical pre-flush strategies and CO₂ storage mechanisms.

Reservoir characteristic	Sandstone formations	Carbonate formations
Mineralogy & geochemical reactivity	Predominantly quartz and silicates; generally low reactivity to injected fluids.	Predominantly calcite and dolomite; highly reactive with acidic fluids (e.g., dissolved CO ₂ , chelants).
Heterogeneity & flow mechanisms	Typically more homogeneous with uniform pore connectivity; dominated by matrix flow.	Highly heterogeneous; often features complex dual-porosity systems and fracture-dominated flow.
Dominant trapping mechanisms	Structural, residual, and solubility trapping dominate due to uniform sweep and limited reactive minerals.	Mineral trapping potential is significantly higher and faster due to abundant reactive Ca- and Mg-bearing minerals.
Pre-flush strategy focus	Enhancing solubility trapping (e.g., low-salinity pre-flush) and mobility control (e.g., nanoparticle-stabilized foams).	Inducing controlled mineral dissolution and providing mobility control to counter fracture channeling (e.g., CO ₂ -soluble surfactants, chelants).
Key risks of pre-flush fluids	Clay swelling, fines migration, and subsequent permeability impairment (especially with low-salinity water).	Rapid dissolution creating preferential flow channels (wormholing) and highly variable surfactant adsorption.

the same salinity reduction that suppresses salt precipitation may destabilize clay minerals and mobilize fines. Another prospect lies in tailor-made surfactant and CO₂-philic formulations capable of tolerating extreme salinity and temperature, supported by recent advances in CO₂-soluble surfactants and environmentally friendly biosurfactants [115]. Nanoparticle technologies, particularly when combined with surfactants, are likely to play a role in enhancing wettability alteration and residual trapping but require pilot-scale demonstrations to confirm scalability [106]. Furthermore, integrated modeling and monitoring that link geochemical simulations, reservoir-scale foam propagation models, and geophysical surveillance will be essential to assess long-term stability and cost-effectiveness [40].

The geological formation type has a significant influence on both the efficacy and security of CO₂ storage when implementing chemical pre-flush techniques. In sandstone formations, high porosity and permeability promote uniform CO₂ distribution and efficient dissolution during freshwater or low-salinity pre-flush operations, with minimal mineral alteration risk [10, 59]. On the other hand, carbonate formations exhibit higher geochemical reactivity, where injected conditioning fluids such as chelating agents or surfactant-based foams can interact with minerals to modify pore structure through dissolution or precipitation, directly affecting long-term storage stability [21, 70]. In heterogeneous or clay-rich aquifers, pre-flush treatments must be applied cautiously, as low-salinity water or chelants

may mobilize fines or induce clay swelling, leading to permeability impairment [112, 116]. Therefore, the choice of pre-flush strategy should be closely aligned with formation mineralogy, clay content, and reactivity, ensuring that the method enhances CO₂ solubility and injectivity without compromising caprock integrity or geochemical stability [50, 117]. To systematically highlight how formation characteristics dictate the selection and success of chemical pre-flush treatments, a direct comparison of sandstone and carbonate reservoirs is summarized in Table 6. This synthesis underscores the necessity of tailoring pre-flush designs to site-specific geochemical and petrophysical conditions.

7 Conclusions

- Enhancing solubility trapping is critical for ensuring long-term CO₂ storage security in deep saline aquifers, as it directly supports both injectivity improvement and mineral trapping.
- Freshwater or low-salinity pre-flush is the simplest and most field-ready approach; it dilutes brine salinity, prevents salt precipitation, and enhances CO₂ dissolution and mineralization. However, its application must be formation-specific because clay swelling, fines migration, and permeability impairment may offset the injectivity benefits.
- Chelating agents (e.g., EDTA, GLDA) prevent scaling by binding multivalent cations, improve injectivity, and release reactive ions that accelerate carbonate precipitation, though high cost and degradation limit field use.
- Nanoparticle-assisted injection modifies interfacial and wettability properties to increase dissolution and stability, with potential for coupling with surfactants, but requires further field validation.
- Surfactant-based CO₂ foams offer the most mature technique for improving sweep efficiency and reducing gas mobility, thereby enhancing residual and solubility trapping under realistic saline conditions.
- Adsorption on carbonate and clay minerals may increase chemical consumption, shorten the effective foam-propagation distance, and cause spatially variable wettability alteration; therefore, adsorption behavior must be included in field-scale transport, stability, and techno-economic evaluations.
- The formation type and geochemical composition (sandstone vs. carbonate) govern pre-flush

performance and storage permanence; strategies must be site-specific to balance dissolution, reactivity, and injectivity.

- Future work should prioritize scalability, cost efficiency, and environmental compatibility, integrating laboratory findings with reservoir-scale modeling and field pilot testing to validate pre-flush effectiveness.

Data Availability Statement

Not applicable.

Funding

This work was supported without any funding.

Conflicts of Interest

Arshad Raza served as an Associate Editor of the *Reservoir Science* at the time of manuscript submission. To ensure the integrity of the peer-review process, Arshad Raza was not involved in the editorial handling, peer review, or decision-making process for this manuscript, which was handled independently by another editor. The remaining authors declare no conflicts of interest.

AI Use Statement

The authors declare that no generative AI was used in the preparation of this manuscript.

Ethical Approval and Consent to Participate

Not applicable. This article is a literature review and does not involve human participants or animals.

References

- [1] Pörtner, H. O., Roberts, D. C., Poloczanska, E. S., Mintenbeck, K., Tignor, M., Alegría, A., ... & Okem, A. (2022). Summary for policymakers. *IPCC 2022: Climate Change 2022: Impacts, Adaptation and Vulnerability. Contribution of Working Group II to the Sixth Assessment Report of the Intergovernmental Panel on Climate Change*, 3-33. [CrossRef]
- [2] Crippa, M., Guizzardi, D., Pagani, F., Banja, M., Muntean, M., Schaaf, E., ... & Pekar, F. (2024). *GHG emissions of all world countries - 2024 Report*. Publications Office of the European Union, Luxembourg. https://edgar.jrc.ec.europa.eu/report_2024
- [3] Friedlingstein, P., O'Sullivan, M., Jones, M. W., Andrew, R. M., Hauck, J., et al. (2025). *Global Carbon*

- Budget 2024. *Earth System Science Data*, 17, 965-1039. [CrossRef]
- [4] Pörtner, H. O., Roberts, D. C., Adams, H., Adler, C., Aldunce, P., Ali, E., ... & Birkmann, J. (2022). Climate change 2022: Impacts, adaptation and vulnerability. *Contribution of Working Group II to the Sixth Assessment Report of the Intergovernmental Panel on Climate Change* (pp. 3-33). Cambridge University Press. [CrossRef]
- [5] Bui, M., Adjiman, C. S., Bardow, A., Anthony, E. J., Boston, A., Brown, S., ... & Mac Dowell, N. (2018). Carbon capture and storage (CCS): the way forward. *Energy & environmental science*, 11(5), 1062-1176. [CrossRef]
- [6] Lackner, K. S. (2003). A guide to CO₂ sequestration. *Science*, 300(5626), 1677-1678. [CrossRef]
- [7] Yasemi, S., Khalili, Y., Sanati, A., & Bagheri, M. (2023). Carbon capture and storage: Application in the oil and gas industry. *Sustainability*, 15(19), 14486. [CrossRef]
- [8] Metz, B., Davidson, O., de Coninck, H. C., Loos, M., & Meyer, L. A. (Eds.) (2005). *IPCC Special Report on Carbon Dioxide Capture and Storage*. Prepared by Working Group III of the Intergovernmental Panel on Climate Change. Cambridge University Press. Retrieved from <https://www.ipcc.ch/report/carbon-dioxide-capture-and-storage/>
- [9] Ali, M., Jha, N. K., Pal, N., Keshavarz, A., Hoteit, H., & Sarmadivaleh, M. (2022). Recent advances in carbon dioxide geological storage, experimental procedures, influencing parameters, and future outlook. *Earth-Science Reviews*, 225, 103895. [CrossRef]
- [10] Michael, K., Golab, A., Shulakova, V., Ennis-King, J., Allinson, G., Sharma, S., & Aiken, T. (2010). Geological storage of CO₂ in saline aquifers-A review of the experience from existing storage operations. *International Journal of Greenhouse Gas Control*, 4(4), 659-667. [CrossRef]
- [11] Bachu, S. (2015). Review of CO₂ storage efficiency in deep saline aquifers. *International Journal of Greenhouse Gas Control*, 40, 188-202. [CrossRef]
- [12] Benson, S. M., & Cole, D. R. (2008). CO₂ sequestration in deep sedimentary formations. *Elements*, 4(5), 325-331. [CrossRef]
- [13] Ringrose, P. S., Furre, A. K., Gilfillan, S. M., Krevor, S., Landrø, M., Leslie, R., ... & Zahid, A. (2021). Storage of carbon dioxide in saline aquifers: physicochemical processes, key constraints, and scale-up potential. *Annual review of chemical and biomolecular engineering*, 12, 471-494. [CrossRef]
- [14] Furre, A.-K., Eiken, O., Alnes, H., Vevatne, J. N., & Kiær, A. F. (2017). 20 years of monitoring CO₂-injection at Sleipner. *Energy Procedia*, 114, 3916-3926. [CrossRef]
- [15] Chadwick, R. A. (2013). Offshore CO₂ storage: Sleipner natural gas field beneath the North Sea. In *Geological Storage of Carbon Dioxide (CO₂)* (pp. 227-253). Woodhead Publishing. [CrossRef]
- [16] Yang, B., Shao, C., Hu, X., Ngata, M. R., & Aminu, M. D. (2023). Advances in carbon dioxide storage projects: Assessment and perspectives. *Energy & Fuels*, 37(3), 1757-1776. [CrossRef]
- [17] De Silva, G. P. D., Ranjith, P. G., & Perera, M. S. A. (2015). Geochemical aspects of CO₂ sequestration in deep saline aquifers: A review. *Fuel*, 155, 128-143. [CrossRef]
- [18] Dutta, R., Singh, R., Chakraborty, R., Kundu, G., & Mandal, A. (2025). Optimisation of CO₂ storage in saline aquifers: A field-scale mechanistic study on injection strategies, pressure management, and long-term containment. *Environmental Earth Sciences*, 84(13), 388. [CrossRef]
- [19] Shukla Potdar, R., & Vishal, V. (2016). Trapping mechanism of CO₂ storage in deep saline aquifers: Brief review. In *Geologic Carbon Sequestration* (pp. 47-58). Springer, Cham. [CrossRef]
- [20] Johnson, J. W., Nitao, J. J., & Knauss, K. G. (2004). Reactive transport modelling of CO₂ storage in saline aquifers to elucidate fundamental processes, trapping mechanisms and sequestration partitioning. *Geological Society, London, Special Publications*, 233, 107-128. [CrossRef]
- [21] Jin, C., Liu, L., Li, Y., & Zeng, R. (2017). Capacity assessment of CO₂ storage in deep saline aquifers by mineral trapping and the implications for Songliao Basin, Northeast China. *Energy Science & Engineering*, 5, 81-89. [CrossRef]
- [22] Celia, M. A., Bachu, S., Nordbotten, J. M., & Bandilla, K. W. (2015). Status of CO₂ storage in deep saline aquifers with emphasis on modeling approaches and practical simulations. *Water Resources Research*, 51(9), 6846-6892. [CrossRef]
- [23] Emami-Meybodi, H., Hassanzadeh, H., Green, C. P., & Ennis-King, J. (2015). Convective dissolution of CO₂ in saline aquifers: Progress in modeling and experiments. *International Journal of Greenhouse Gas Control*, 40, 238-266. [CrossRef]
- [24] Duan, Z., & Sun, R. (2003). An improved model calculating CO₂ solubility in pure water and aqueous NaCl solutions from 273 to 533 K and from 0 to 2000 bar. *Chemical Geology*, 193, 257-271. [CrossRef]
- [25] Muller, N., Qi, R., Mackie, E., Pruess, K., & Blunt, M. J. (2009). CO₂ injection impairment due to halite precipitation. *Energy Procedia*, 1(1), 3507-3514. [CrossRef]
- [26] Pruess, K., & Müller, N. (2009). Formation dry-out from CO₂ injection into saline aquifers: 1. Effects of solids precipitation and their mitigation. *Water Resources Research*, 45(3). [CrossRef]
- [27] Yan, L., Niftaliyev, R., Voskov, D., & Farajzadeh, R. (2025). Dynamics of salt precipitation at pore scale during CO₂ subsurface storage in saline aquifer.

- Journal of Colloid and Interface Science*, 678, 419-430. [CrossRef]
- [28] Xu, R., Li, R., Ma, J., He, D., & Jiang, P. (2017). Effect of mineral dissolution/precipitation and CO₂ exsolution on CO₂ transport in geological carbon storage. *Accounts of Chemical Research*, 50(9), 2056-2066. [CrossRef]
- [29] Miri, R., & Hellevang, H. (2016). Salt precipitation during CO₂ storage-A review. *International Journal of Greenhouse Gas Control*, 51, 136-147. [CrossRef]
- [30] Nasiri, M. R., Rostami, B., Keramati Nejad, M., Riahi, S., Fathollahi, A., & Al-Masri, W. F. (2025). Experimental investigation of the intermittent injection of brine-scCO₂ to mitigate salt precipitation during CO₂ storage in saline aquifers. *International Journal of Greenhouse Gas Control*, 144, 104379. [CrossRef]
- [31] Papi, A., Jahanbakhsh, A., & Maroto-Valer, M. M. (2025). Preventing salt precipitation in CO₂ storage processes in saline aquifers: Dissolved-water CO₂ injection method. *Energy & Fuels*, 39(8), 3926-3941. [CrossRef]
- [32] Smith, N., Boone, P., Oguntimehin, A., van Essen, G., Guo, R., Reynolds, M. A., Friesen, L., Cano, M. C., & O'Brien, S. (2022). Quest CCS facility: Halite damage and injectivity remediation in CO₂ injection wells. *International Journal of Greenhouse Gas Control*, 119, 103718. [CrossRef]
- [33] Kleinitz, W., Dietzsch, G., & Köhler, M. (2003). Halite scale formation in gas-producing wells. *Chemical Engineering Research and Design*, 81(3), 352-358. [CrossRef]
- [34] Kim, M. J., & Jeon, J. (2020). Effects of Ca-ligand stability constant and chelating agent concentration on the CO₂ storage using paper sludge ash and chelating agent. *Journal of CO₂ Utilization*, 40, 101202. [CrossRef]
- [35] Wang, J., Sekia, R., Tamura, R., & Watanabe, N. (2024). CO₂ capture, geological storage, and mineralization using biobased biodegradable chelating agents and seawater. *Science Advances*, 10(46), eadq0515. [CrossRef]
- [36] Zhao, H., Park, Y., Lee, D. H., & Park, A. H. A. (2013). Tuning the dissolution kinetics of wollastonite via chelating agents for CO₂ sequestration with integrated synthesis of precipitated calcium carbonates. *Physical Chemistry Chemical Physics*, 15(36), 15185-15192. [CrossRef]
- [37] Alzobaidi, S., Lotfollahi, M., Kim, I., Johnston, K. P., & DiCarlo, D. A. (2017). Carbon dioxide-in-brine foams at high temperatures and extreme salinities stabilized with silica nanoparticles. *Energy & Fuels*, 31(10), 10680-10690. [CrossRef]
- [38] Guo, F., Aryana, S. A., Wang, Y., McLaughlin, J. F., & Coddington, K. (2019). Enhancement of storage capacity of CO₂ in megaporous saline aquifers using nanoparticle-stabilized CO₂ foam. *International Journal of Greenhouse Gas Control*, 87, 134-141. [CrossRef]
- [39] Rathnaweera, T. D., & Ranjith, P. G. (2020). Nano-modified CO₂ for enhanced deep saline CO₂ sequestration: A review and perspective study. *Earth-Science Reviews*, 200, 103035. [CrossRef]
- [40] Burrows, L. C., Haeri, F., Tapriyal, D., Shah, P. G., Crandall, D., Enick, R. M., & Goodman, A. (2023). CO₂-soluble nonionic surfactants for enhanced CO₂ storage via in situ foam generation. *Energy & Fuels*, 37(16), 12089-12100. [CrossRef]
- [41] Føyen, T., Brattekkås, B., Fernø, M. A., Barrabino, A., & Holt, T. (2020). Increased CO₂ storage capacity using CO₂-foam. *International Journal of Greenhouse Gas Control*, 96, 103016. [CrossRef]
- [42] Wu, Q., Ding, L., Zhao, L., Alhashboul, A. A., Almajid, M. M., Patil, P., Zhao, W., & Fan, Z. (2024). CO₂ soluble surfactants for carbon storage in carbonate saline aquifers with achievable injectivity: Implications from the continuous CO₂ injection study. *Energy*, 290, 130064. [CrossRef]
- [43] Iranzi, J., Rwabuhungu Rwatangabo, D. E., & Son, H. (2025). Evaluation of the physical and economic potential of surfactant-based CO₂ capture and storage in a saline aquifer. *Journal of Industrial and Engineering Chemistry*, 147, 259-277. [CrossRef]
- [44] Lyu, X., Voskov, D., & Rossen, W. R. (2021). Numerical investigations of foam-assisted CO₂ storage in saline aquifers. *International journal of greenhouse gas control*, 108, 103314. [CrossRef]
- [45] Hosa, A., Esentia, M., Stewart, J., & Haszeldine, S. (2011). Injection of CO₂ into saline formations: Benchmarking worldwide projects. *Chemical Engineering Research and Design*, 89(9), 1855-1864. [CrossRef]
- [46] Kikuta, K., Hongo, S., Tanase, D., & Ohsumi, T. (2005). Field test of CO₂ injection in Nagaoka, Japan. In *Greenhouse Gas Control Technologies 7* (pp. 1367-1372). Elsevier. [CrossRef]
- [47] Kalam, S., Olayiwola, T., Al-Rubaii, M. M., Amaechi, B. I., Jamal, M. S., & Awotunde, A. A. (2021). Carbon dioxide sequestration in underground formations: Review of experimental, modeling, and field studies. *Journal of Petroleum Exploration and Production Technology*, 11(1), 303-325. [CrossRef]
- [48] Szymczak, P. D. (2025, January 15). Aramco, Linde, SLB ink agreement to build Saudi CCS hub [Industry news]. *Journal of Petroleum Technology (SPE)*. Retrieved from <https://jpt.spe.org/aramco-linde-slb-ink-agreement-to-build-saudi-ccs-hub>
- [49] Chadwick, A., Arts, R., Bernstone, C., May, F., Thibeau, S., & Zweigel, P. (2008). *Best practice for the storage of CO₂ in saline aquifers-observations and guidelines from the SACS and CO2STORE projects* (Vol. 14). British Geological Survey. <http://nora.nerc.ac.uk/id>

/eprint/2959/

- [50] Shiran, B. S., Sadaak, B., Solbakken, J., Toigo, C., & Zamani, N. (2024). Impact of salt precipitation on porosity-permeability correlations: Implications for CO₂ storage. In *Fifth EAGE Global Energy Transition Conference & Exhibition (GET 2024)* (pp. 1-5). EAGE. [CrossRef]
- [51] Luo, A., Li, Y., Chen, X., Zhu, Z., & Peng, Y. (2022). Review of CO₂ sequestration mechanism in saline aquifers. *Natural Gas Industry B*, 9(4), 383-393. [CrossRef]
- [52] Khan, A., Khan, F., Marapira, T. R., Alafnan, S., Raza, A., Mahmoud, M., & Kamal, M. S. (2026). A review on CO₂ mineralization in saline aquifers: Advances, challenges, and future prospects for sustainable carbon sequestration. *Journal of Environmental Management*, 397, 128358. [CrossRef]
- [53] Kearns, J., Teletzke, G., Palmer, J., Thomann, H., Khesghi, H., Chen, Y.-H. H., Paltsev, S., & Herzog, H. (2017). Developing a consistent database for regional geologic CO₂ storage capacity worldwide. *Energy Procedia*, 114, 4697-4709. [CrossRef]
- [54] Knopf, S., & May, F. (2017). Comparing methods for the estimation of CO₂ storage capacity in saline aquifers in Germany: Regional aquifer based vs. structural trap based assessments. *Energy Procedia*, 114, 4710-4721. [CrossRef]
- [55] Bachu, S., & Bennion, D. B. (2009). Dependence of CO₂-brine interfacial tension on aquifer pressure, temperature and water salinity. *Energy Procedia*, 1(1), 3157-3164. [CrossRef]
- [56] Nordbotten, J. M., Celia, M. A., & Bachu, S. (2005). Injection and storage of CO₂ in deep saline aquifers: Analytical solution for CO₂ plume evolution during injection. *Transport in Porous Media*, 58(3), 339-360. [CrossRef]
- [57] Rutqvist, J. (2012). The geomechanics of CO₂ storage in deep sedimentary formations. *Geotechnical and Geological Engineering*, 30(3), 525-551. [CrossRef]
- [58] Li, H., Wang, Z., & Wang, C. (2025). Assessing CO₂ storage potential in saline aquifers with low porosity and strong heterogeneity in Permian Shiqianfeng formation in the Yulin area, Ordos Basin: Optimization based on a 3D geological model constrained by horizontal probability trend. *Environmental Earth Sciences*, 84(12), 329. [CrossRef]
- [59] Eccles, J. K., Pratson, L., Newell, R. G., & Jackson, R. B. (2009). Physical and economic potential of geological CO₂ storage in saline aquifers. *Environmental Science & Technology*, 43(6), 1962-1969. [CrossRef]
- [60] Wu, W., Zhou, N., Zhu, X., & Bai, M. (2025). Research on the rock pore structure and porosity-permeability characteristics of oilfield saline aquifer CCS. *Chemistry and Technology of Fuels and Oils*, 60(6), 1562-1568. [CrossRef]
- [61] Krevor, S., Blunt, M. J., Benson, S. M., Pentland, C. H., Reynolds, C., Al-Menhali, A., & Niu, B. (2015). Capillary trapping for geologic carbon dioxide storage-From pore scale physics to field scale implications. *International Journal of Greenhouse Gas Control*, 40, 221-237. [CrossRef]
- [62] Gaus, I. (2010). Role and impact of CO₂-rock interactions during CO₂ storage in sedimentary rocks. *International journal of greenhouse gas control*, 4(1), 73-89. [CrossRef]
- [63] Kumar, V., Ren, G., Talabi, O., Misra, S., Odi, U., Silver, A., Gupta, A., & Temizel, C. (2024). Geological carbon storage in saline aquifers: Factors governing residual & solubility trapping. In *Abu Dhabi International Petroleum Exhibition and Conference (ADIPEC)*. SPE-222767-MS. [CrossRef]
- [64] Khan, A., Alafnan, S. F., Raza, A., Marapira, T. R., & Murtaza, M. (2025). Enforced carbon mineralization: Unlocking CO₂ storage potential in saline aquifers. In *SPE Offshore Europe Conference & Exhibition*. SPE-226713-MS. [CrossRef]
- [65] Kelemen, P., Benson, S. M., Pilorgé, H., Psarras, P., & Wilcox, J. (2019). An overview of the status and challenges of CO₂ storage in minerals and geological formations. *Frontiers in Climate*, 1, 9. [CrossRef]
- [66] Pentland, C. H., El-Maghraby, R., Iglauer, S., & Blunt, M. J. (2011). Measurements of the capillary trapping of super-critical carbon dioxide in Berea sandstone. *Geophysical Research Letters*, 38(6). [CrossRef]
- [67] Luquot, L., & Gouze, P. (2009). Experimental determination of porosity and permeability changes induced by injection of CO₂ into carbonate rocks. *Chemical Geology*, 265(1-2), 148-159. [CrossRef]
- [68] Spycher, N., Pruess, K., & Ennis-King, J. (2003). CO₂-H₂O mixtures in the geological sequestration of CO₂. I. Assessment and calculation of mutual solubilities from 12 to 100 °C and up to 600 bar. *Geochimica et Cosmochimica Acta*, 67(16), 3015-3031. [CrossRef]
- [69] Duan, Z., Sun, R., Zhu, C., & Chou, I. M. (2006). An improved model for the calculation of CO₂ solubility in aqueous solutions containing Na⁺, K⁺, Ca²⁺, Mg²⁺, Cl⁻, and SO₄²⁻. *Marine Chemistry*, 98(2-4), 131-139. [CrossRef]
- [70] Chen, Y., Saeedi, A., & Xie, Q. (2023). Interfacial interactions of CO₂-brine-rock system in saline aquifers for CO₂ geological storage: A critical review. *International Journal of Coal Geology*, 274, 104272. [CrossRef]
- [71] Michel-Meyer, I., Shavit, U., Tsinober, A., & Rosenzweig, R. (2020). The role of water flow and dispersive fluxes in the dissolution of CO₂ in deep saline aquifers. *Water Resources Research*, 56(11), e2020WR028184. [CrossRef]
- [72] Zuo, L., Krevor, S., Falta, R. W., & Benson, S. M. (2012). An experimental study of CO₂ exsolution and relative permeability measurements during CO₂

- saturated water depressurization. *Transport in porous media*, 91(2), 459-478. [CrossRef]
- [73] Khanal, A., Khan, M. I., & Shahriar, M. F. (2024). Comprehensive parametric study of CO₂ sequestration in deep saline aquifers. *Chemical Engineering Science*, 287, 119734. [CrossRef]
- [74] Edem, D. E., Abba, M. K., Nourian, A., Babaie, M., & Naeem, Z. (2022). Experimental study on the interplay between different brine types/concentrations and CO₂ injectivity for effective CO₂ storage in deep saline aquifers. *Sustainability*, 14(2), 986. [CrossRef]
- [75] Liu, Y., Hou, M., Yang, G., & Han, B. (2011). Solubility of CO₂ in aqueous solutions of NaCl, KCl, CaCl₂ and their mixed salts at different temperatures and pressures. *The Journal of Supercritical Fluids*, 56(2), 125-129. [CrossRef]
- [76] Liu, B., Mahmood, B. S., Mohammadian, E., Khaksar Manshad, A., Rosli, N. R., & Ostadhassan, M. (2021). Measurement of solubility of CO₂ in NaCl, CaCl₂, MgCl₂ and MgCl₂ + CaCl₂ brines at temperatures from 298 to 373 K and pressures up to 20 MPa using the potentiometric titration method. *Energies*, 14(21), 7222. [CrossRef]
- [77] Zhao, H., Fedkin, M. V., Dilmore, R. M., & Lvov, S. N. (2015). Carbon dioxide solubility in aqueous solutions of sodium chloride at geological conditions: Experimental results at 323.15, 373.15, and 423.15 K and 150 bar and modeling up to 573.15 K and 2000 bar. *Geochimica et Cosmochimica Acta*, 149, 165-189. [CrossRef]
- [78] Edem, D., Abba, M., Nourian, A., Babaie, M., & Mohammed, N. (2020). The effects of different salt types and concentration on CO₂ injectivity during CO₂ sequestration in deep saline aquifers. In *SPE Nigeria Annual International Conference and Exhibition*. SPE-203744-MS. [CrossRef]
- [79] Rosenbauer, R. J., Koksalan, T., & Palandri, J. L. (2005). Experimental investigation of CO₂-brine-rock interactions at elevated temperature and pressure: Implications for CO₂ sequestration in deep-saline aquifers. *Fuel Processing Technology*, 86(14-15), 1581-1597. [CrossRef]
- [80] Deng, K., Lin, Y., Ning, H., Liu, W., Singh, A., & Zhang, G. (2018). Influences of temperature and pressure on CO₂ solubility in saline solutions in simulated oil and gas well environments. *Applied Geochemistry*, 99, 22-30. [CrossRef]
- [81] Marapira, T., Alafnan, S., Raza, A., Mahmoud, M., Murtaza, M., & Kamal, M. S. (2025). Accelerated CO₂ dissolution and mineralization in saline aquifers using alkaline earth metals. *Chemical Engineering Journal*, 523, 168207. [CrossRef]
- [82] Hassanzadeh, H., Pooladi-Darvish, M., & Keith, D. W. (2009). Accelerating CO₂ dissolution in saline aquifers for geological storage-Mechanistic and sensitivity studies. *Energy & Fuels*, 23(6), 3328-3336. [CrossRef]
- [83] Sun, X., Ning, H., Shi, Y., Yu, G., Jia, Z., Han, M., & Zhang, Y. (2023). Study of CO₂ solubility enhancement by nanomaterials in carbonated water: Implications for enhanced oil recovery and CO₂ storage. *Journal of Cleaner Production*, 396, 136562. [CrossRef]
- [84] Chen, Y., Chen, S., Li, D., & Jiang, X. (2023). Density-driven convection for CO₂ solubility trapping in saline aquifers: Modeling and influencing factors. *Geotechnics*, 3(1), 70-103. [CrossRef]
- [85] Wang, J., Watanabe, N., Inomoto, K., Kamitakahara, M., Nakamura, K., Komai, T., & Tsuchiya, N. (2021). Enhancement of aragonite mineralization with a chelating agent for CO₂ storage and utilization at low to moderate temperatures. *Scientific Reports*, 11(1), 13956. [CrossRef]
- [86] LePage, J. N., De Wolf, C., Bemelaar, J., & Nasr-El-Din, H. A. (2011). An environmentally friendly stimulation fluid for high-temperature applications. *SPE Journal*, 16(1), 104-110. [CrossRef]
- [87] Smith, R. M., & Martell, A. E. (1987). Critical stability constants, enthalpies and entropies for the formation of metal complexes of aminopolycarboxylic acids and carboxylic acids. *Science of the Total Environment*, 64(1-2), 125-147. [CrossRef]
- [88] Martell, A. E., & Hancock, R. D. (1996). *Metal Complexes in Aqueous Solutions*. Springer US, Boston, MA. [CrossRef]
- [89] Almubarak, T., Ng, J. H., & Nasr-El-Din, H. (2017). Chelating agents in productivity enhancement: A review. In *SPE Oklahoma City Oil and Gas Symposium*. SPE-185097-MS. [CrossRef]
- [90] Martell, A. E., & Calvin, M. (1952). *Chemistry of the Metal Chelate Compounds*. Prentice-Hall, New York. <https://archive.org/details/chemistryofmetal00mart/page/n1/mode/2up>
- [91] Calvin, M., & Melchior, N. C. (1948). Stability of chelate compounds. IV. Effect of the metal ion. *Journal of the American Chemical Society*, 70(10), 3270-3273. [CrossRef]
- [92] Cihan, A., Petrusak, R., Bhuvankar, P., Alumbaugh, D., Trautz, R., & Birkholzer, J. T. (2022). Permeability decline by clay fines migration around a low-salinity fluid injection well. *Groundwater*, 60(1), 87-98. [CrossRef]
- [93] Fredd, C. N., & Fogler, H. S. (1998). The influence of chelating agents on the kinetics of calcite dissolution. *Journal of Colloid and Interface Science*, 204(1), 187-197. [CrossRef]
- [94] Hassan, A., Mahmoud, M., Bageri, B. S., Aljawad, M. S., Kamal, M. S., Barri, A. A., & Hussein, I. A. (2020). Applications of chelating agents in the upstream oil and gas industry: A review. *Energy & Fuels*, 34(12), 15593-15613. [CrossRef]

- [95] Javadpour, F., & Nicot, J.-P. (2011). Enhanced CO₂ storage and sequestration in deep saline aquifers by nanoparticles: Commingled disposal of depleted uranium and CO₂. *Transport in Porous Media*, 89(2), 265-284. [CrossRef]
- [96] Sadraei, R., Cucchiara, F., Magnacca, G., & Testa, M. L. (2021). Surface functionalization of handleable silica-based mesoporous materials for CO₂ sequestration: Synthesis, characterization and performance. *Surfaces and Interfaces*, 27, 101542. [CrossRef]
- [97] Chaudhry, A. U., Muneer, R., Lashari, Z. A., Hashmet, M. R., Osei-Bonsu, K., Abdala, A., & Rabbani, H. S. (2024). Recent advancements in novel nanoparticles as foam stabilizer: Prospects in EOR and CO₂ sequestration. *Journal of Molecular Liquids*, 407, 125209. [CrossRef]
- [98] Ikeda, K., Shimoyama, Y., & Orita, Y. (2023). Efficient purification of surface modified nanoparticles from its nanosuspension by using supercritical CO₂ technology. *The Journal of Supercritical Fluids*, 199, 105966. [CrossRef]
- [99] Li, X., Peng, B., Liu, Q., Liu, J., & Shang, L. (2023). Micro and nanobubbles technologies as a new horizon for CO₂-EOR and CO₂ geological storage techniques: A review. *Fuel*, 341, 127661. [CrossRef]
- [100] Gang, S., Kang, I., Lee, J., & Jung, J. (2025). Effect of surface-treated silica nanofluid on supercritical CO₂ injection efficiency: Application to deep saline aquifers. *Journal of CO₂ Utilization*, 97, 103103. [CrossRef]
- [101] Youns, Y. T., Manshad, A. K., & Ali, J. A. (2023). Sustainable aspects behind the application of nanotechnology in CO₂ sequestration. *Fuel*, 349, 128680. [CrossRef]
- [102] Da, C., Alzobaidi, S., Jian, G., Zhang, L., Biswal, S. L., Hirasaki, G. J., & Johnston, K. P. (2018). Carbon dioxide/water foams stabilized with a zwitterionic surfactant at temperatures up to 150 °C in high salinity brine. *Journal of Petroleum Science and Engineering*, 166, 880-890. [CrossRef]
- [103] Alzobaidi, S., Da, C., Tran, V., Prodanović, M., & Johnston, K. P. (2017). High temperature ultralow water content carbon dioxide-in-water foam stabilized with viscoelastic zwitterionic surfactants. *Journal of colloid and interface science*, 488, 79-91. [CrossRef]
- [104] Chen, Y., Elhag, A. S., Cui, L., Worthen, A. J., Reddy, P. P., Noguera, J. A., ... & Johnston, K. P. (2015). CO₂-in-water foam at elevated temperature and salinity stabilized with a nonionic surfactant with a high degree of ethoxylation. *Industrial & Engineering Chemistry Research*, 54(16), 4252-4263. [CrossRef]
- [105] Føyen, T., Alcorn, Z. P., Fernø, M. A., Barrabino, A., & Holt, T. (2021). CO₂ mobility reduction using foam stabilized by CO₂-and water-soluble surfactants. *Journal of Petroleum Science and Engineering*, 196, 107651. [CrossRef]
- [106] Li, W., Wei, F., Xiong, C., Ouyang, J., Shao, L., Dai, M., Liu, P., & Du, D. (2019). A novel supercritical CO₂ foam system stabilized with a mixture of zwitterionic surfactant and silica nanoparticles for enhanced oil recovery. *Frontiers in Chemistry*, 7, 718. [CrossRef]
- [107] Varghese, A. M., Ahmed, S., Stefanopoulos, K. L., Alamoodi, N., Alameri, W., & Karanikolos, G. N. (2025). Nanomaterials as CO₂ foam stabilizers: A comprehensive review. *Journal of Molecular Liquids*, 436, 128156. [CrossRef]
- [108] Hansen, O., Gilding, D., Nazarian, B., Osdal, B., Ringrose, P., Kristoffersen, J. B., ... & Hansen, H. (2013). Snøhvit: The history of injecting and storing 1 Mt CO₂ in the fluvial Tubaen Fm. *Energy procedia*, 37, 3565-3573. [CrossRef]
- [109] Ding, L., AlSofi, A. M., AlMajid, M. M., & Patil, P. (2024). CO₂ soluble surfactants assisted carbon storage under achievable pressure gradients: Effect of surfactant partitioning behavior during continuous CO₂ injection. In *International Petroleum Technology Conference*. IPTC-23958-MS. [CrossRef]
- [110] Ghaffour, N., Missimer, T. M., & Amy, G. L. (2013). Technical review and evaluation of the economics of water desalination: Current and future challenges for better water supply sustainability. *Desalination*, 309, 197-207. [CrossRef]
- [111] Zarzo, D., & Prats, D. (2018). Desalination and energy consumption. What can we expect in the near future?. *Desalination*, 427, 1-9. [CrossRef]
- [112] Xie, Q., Saeedi, A., Delle Piane, C., Esteban, L., & Brady, P. V. (2017). Fines migration during CO₂ injection: Experimental results interpreted using surface forces. *International Journal of Greenhouse Gas Control*, 65, 32-39. [CrossRef]
- [113] Fredd, C. N., & Fogler, H. S. (1998). Alternative stimulation fluids and their impact on carbonate acidizing. *SPE Journal*, 3(1), 34-41. [CrossRef]
- [114] Talebian, S. H., Masoudi, R., Tan, I. M., & Zitha, P. L. J. (2014). Foam assisted CO₂-EOR: A review of concept, challenges, and future prospects. *Journal of Petroleum Science and Engineering*, 120, 202-215. [CrossRef]
- [115] Liang, S., Luo, W., Luo, Z., Wang, W., Xue, X., & Dong, B. (2023). Research of CO₂-soluble surfactants for enhanced oil recovery: Review and outlook. *Molecules*, 28(24), 8042. [CrossRef]
- [116] Sokama-Neuyam, Y. A., Ginting, P. U. R., Timilsina, B., & Ursin, J. R. (2017). The coupled effect of fines mobilization and salt precipitation on CO₂ injectivity. *Energies*, 10(8), 1125. [CrossRef]
- [117] Kampman, N., Busch, A., Bertier, P., Snippe, J., Hangx, S., Pipich, V., ... & Bickle, M. J. (2016). Observational evidence confirms modelling of the long-term integrity of CO₂-reservoir caprocks. *Nature Communications*, 7(1), 12268. [CrossRef]



Mohammed Mahtab Ahmed received the M.S. degree in Petroleum Engineering from King Fahd University of Petroleum & Minerals (KFUPM), Saudi Arabia, in 2026. His research focused on CO₂ mineralization and storage in deep saline aquifers. His work investigated the use of biodegradable chelating agents, including EDTA and GLDA, to reduce salt precipitation, improve CO₂ solubility and injectivity, and enhance storage capacity. His research integrated high-pressure solubility tests, core-flooding experiments, and advanced characterization techniques, including ICP spectroscopy, X-ray CT, sonic velocity measurements, and low-field NMR. (Email: g202320030@kfupm.edu.sa)



Arshad Raza (Assistant Professor, KFUPM) received the Ph.D. degree in Petroleum Engineering from Curtin University, Australia, in 2017. His research interests include carbon capture, utilization and storage, subsurface hydrogen production and storage, reactive flow dynamics, rock-fracturing techniques, and the assessment of geological media for natural hydrogen. (Email: arshad.raza@kfupm.edu.sa)



Amjed Mohammed Hassan (Research Engineer III, KFUPM) received his Ph.D. in Petroleum Engineering from King Fahd University of Petroleum & Minerals (KFUPM), Saudi Arabia, in 2020. His research interests include petrophysics, unconventional resource development, rock-fluid interactions, and formation damage. He has published more than 90 articles in peer-reviewed journals and international conferences and holds several patents. (Email: amjed.mohammed@kfupm.edu.sa)



Rahul Gajbhiye (Associate Professor, KFUPM) received his Ph.D. in Petroleum Engineering from Louisiana State University, USA, in 2011. His research interests include enhanced oil recovery, multiphase flow in pipes, hydraulic fracturing, drilling fluids, and cementation. Prior to joining KFUPM, he was a Postdoctoral Research Associate at the Tulsa University Drilling Research Project, USA. (Email: rahulg@kfupm.edu.sa)



Fahad Khan (Researcher, KFUPM) received his Ph.D. in Petroleum Engineering from King Fahd University of Petroleum & Minerals (KFUPM), Saudi Arabia, in 2026. His research focuses on unconventional reservoir stimulation, petrophysics and rock mechanics, underground gas storage, thermochemical fluids, and geothermal energy. His work combines laboratory experimentation with numerical modelling to develop innovative stimulation methods for unconventional hydrocarbon and geothermal reservoirs. He holds several U.S. patents and serves as a reviewer for international scientific journals. (Email: fahad.khan@kfupm.edu.sa)



Mohamed Mahmoud (Distinguished Professor, KFUPM) received the Ph.D. degree in Petroleum Engineering from Texas A&M University, USA, in 2011. His research interests include well stimulation, formation damage, enhanced oil recovery, drilling fluids, hole-cleaning modeling in deviated and horizontal wells, advanced petrophysics, and multiphase flow. (Email: mmahmoud@kfupm.edu.sa)